



Ornamental Aluminum Fencing

Aluminum Fence Specs

PICKETS:

5/8" x 5/8" 6063-T6 aluminum. Wall thickness .050". Spacing is 3-13/16".

STRINGERS:

1" x 1" x 72" long. Top thickness .055". Side thickness .085".

SCREWS:

All assembled panels include stainless steel screws with painted heads.









✓ Meets B.O.C.A Pool Code

STYLE	48"	54"	60"
1104	~		
1105			~
2104	~		
21045		•	
2105			0


















1104 / 1105

4' & 51/2'

2104 / 2105

4' & 5'

21045

4' & 5'

Aluminum Post & Gate Specs

POSTS:

2" x 2" line, corner, and end posts are .060" thick. Gate posts are .125" thick.

GATES:

TIG welded construction. Furnished with self-closing hinges.

MISC:

All posts include caps. All screws included with job kit orders.



KEEP IN MIND:


All fencing components are powder coated after punching and notching are completed





✓ Meets B.O.C.A Pool Code

STYLE	48"	54"	60"
2204	>		
22045		9	
2205			•
2224	•		













2204 / 2205

4' & 51/2'

22045

4' & 51/2'

2224

4' & 51/2'





ARMOR-CLAD FENCE is a family-owned and operated business that has been manufacturing quality aluminum fencing in North Carolina since 2003.

ARMOR-CLAD FENCE, LLC

CONTACT • 704.282.4424

Presented By Authorized Dealer For ARMOR-CLAD FENCE